



# BASIC

## Solidity of traffic mirrors

With our Basic Stainless-Steel Mirror, we combine the advantages of the brilliant stainless-steel reflection image with the impact-resistant and shock-proof lightweight construction of UV-resistant synthetic material. This mirror is also available with anti-fog and anti-frost protection – thanks to our patented gel-technology, no power connection is needed – to allow you to use this mirror all year round.

Especially for foggy regions we recommend these mirrors with our special Lotos-Coating.

All our Basic mirrors are equipped with a striking red and white frame for optimum visibility. Of course, we also provide the requisite mounting materials (suitable for bars with a 60 – 90 mm diameter) and may ship all parts individually if requested.

	product code	optics (mm)	parcel size (mm)	weight (kg)	viewing distance	field of application
ice-free	VBB450	450x600	85x85	15	0-10	driveways
	VBB600	600x800	110x90	20	0-15	community roads
	VBB700	oval 700x900	125x100	29	0-20	community roads country roads
	VBB800	800x1000	125x100	31	0-25	country roads
	VBBR60	Ø 600	85x85	18	0-10	driveways
	VBBR80	Ø 800	110x100	23	0-20	community roads
	Lotos	VLB450	450x600	85x85	7,5	0-10
VLB600		600x800	110x90	10	0-15	community roads
VLB700		oval 700x900	125x100	16	0-20	community roads country roads
VLB800		800x1000	125x100	11	0-25	country roads
VLBR60		Ø 600	85x85	8,5	0-10	driveways
VLBR80		Ø 800	110x100	14	0-20	community roads
standard		VEB450	450x600	85x85	6,5	0-10
	VEB600	600x800	110x90	9	0-15	community roads
	VEB700	oval 700x900	125x100	15	0-20	community roads country roads
	VEB800	800x1000	125x100	10	0-25	country roads
	VEBR60	Ø 600	85x85	7,5	0-10	driveways
	VEBR80	Ø 800	110x100	13	0-20	community roads



**We recommend our Basic-mirrors for communities and municipalities !**